

	CHF	\$	€	£
<b>385Z-05226 E12S</b> VR Speed Sensor. -20 .. +100 °C, PU cable 1 m long, green Housing M12x1mm, 60 mm long	61.-	55.-	38.-	31.-
<b>385Z-05227 E58S</b> VR Speed Sensor. -20 .. +100 °C, PU cable 1 m long, green Housing 5/8" 18UNF-2A, 60 mm long	67.-	60.-	42.-	34.-
<b>385Z-05320 E12A *)</b> VR Speed Sensor. -20 .. +100 °C, with Connector M12 for cable 820A-37337 Housing M12x1mm, 60 mm long	58.-	52.-	36.-	29.-
<b>385Z-05321 E58A *)</b> VR Speed Sensor. -20 .. +100 °C, with Connector M12 for cable 820A-37337 Housing 5/8" 18UNF-2A, 60 mm long	63.-	57.-	39.-	32.-
<b>385Z-05331 F12S</b> Halleffect Sensor. -20 .. +100 °C, PU cable 1 m long, green Housing M12x1mm, 60 mm long	63.-	57.-	39.-	32.-
<b>385Z-05332 F58S</b> Halleffect Sensor. -20 .. +100 °C, PU cable 1 m long, green Housing 5/8" 18UNF-2A, 60 mm long	69.-	62.-	43.-	35.-
<b>385Z-05322 F12A *)</b> Halleffect Sensor. -20 .. +100 °C, with Connector M12 for cable 820A-37337 Housing M12x1mm, 60 mm long	60.-	54.-	38.-	30.-
<b>385Z-05323 F58A *)</b> Halleffect Sensor. -20 .. +100 °C, with Connector M12 for cable 820A-37337 Housing 5/8" 18UNF-2A, 60 mm long	68.-	61.-	43.-	34.-
<b>385Z-05334 D12P</b> Differential Halleffect Sensor with Ampl. Push Pull Output Housing M12 x1mm, 60 mm long, Cable with connector (AMP 3Pin) ~350 mm long	77.-	69.-	48.-	39.-
<b>385Z-05335 Y12AD *)</b> Speed and Direction sensor. -20 .. +100°C Housing M12x1 mm 74mm long, with connector M12 Supply 11 .. 32 VDC. Open Collector output	139.-	125.-	87.-	70.-
<b>385Z-05333 D12A *)</b> Differential Halleffect Sensor. -20 .. +100°C Flashed housing with connector M12 Supply 10 .. 30 VDC. Push-Pull Output	77.-	69.-	48.-	39.-
<b>820A-37337 C20A Cable with connector</b> 2 m PU cable with connector, max. Temp. +100°C For the connectio of this Sensors *)	35.-	32.-	22.-	18.-